DIVERSIFIED AIR SYSTEMS, INC.

**FLOTOWER

Ambient Air Cleaner

- Collects dust, fumes, smoke, and odors
- Flexible filter combinations
- Plug & Play Floor Mounted Air Cleaner



- Improves Air Quality, Reduces Heating and AC Costs
- Modular Design, Expandable in Field
- Easy to Install, Easy to Maintain

Ambient Air Cleaner

MAXFLO-TOWER AMBIENT AIR CLEANER

Diversified Air Systems, Inc. now offers an easy to use free-standing ambient air cleaner. The MAXFLO-Tower free standing ambient air cleaner is easy-maintenance, cost-effective industrial air cleaner which uses standard 24 x 24 x 6 inch MERV 11 filters for most applications. In addition, standard size application-specific filter panels may be used for various kinds of contaminants. The filters are in full view and completely accessible: as soon as a filter is full, it simply slides out laterally for easy replacement or cleaning. The MAXFLO-Tower may be hung from the ceiling to conserve floor space, or sit on its base, with up to 3 filter modules. Each module measures 31 x 31 x 24 inches, and has four easy access 24 x 24 x 6 inch filter slots. Charcoal and HEPA filters are available.

OUTSTANDING MAXFLO-TOWER FEATURES



MAXFLO-TOWER II

The MAXFLO-Tower Air Filtration Process:

Airborne contaminates are drawn into the four-sided air intake filtration modules. Contaminates are filtered and the cleaned air is then exhausted on top of the unit. The exhausted clean air creates downward airflow forcing contaminated air downward into the filtration modules. This airflow pattern not only cleans the air but helps stratify the air which reduces heating and cooling costs.

TYPICAL APPLICATION FOR THE MAXFLO-TOWER AMBIENT AIR CLEANER

Dust
 Fumes
 Powders
 Sanding & Welding
 Grinding
 Odors, etc.

Made in USA
1 YEAR LIMITED WARRANTY

CALL TODAY: 800-264-8958

Specifications:

Air flow2500 CFM (3/4 HP) 5000 CFM (3 HP)

4000 CFM (3 HP with AD after filter)

Construction..... 16 ga. welded zinc-coated steel, powder coated

cabinet. Acoustical lining in plenum and blower compartment. Four filter compartments per

Tower module.

Electrical......Tower I, standard: 115/1/60, 11.4 amps, 3/4 HP

Tower II & III, standard: 208-230/460/3/60,

7.8-7.2/4 amps, 3 HP

Optional: 230/1/60, 11.7 amps, 3 HP

Weight (lbs.)..... Tower I: 312, Tower II: 394, Tower III: 455

Sound Level......68 dBA (3/4 HP), 77 dBA (3 HP)


Motor/blower Tower II & III: Dynamically balanced, BI

Tower I: 2-speed forward curve, direct-drive


Filhou Cot Configurations		Filter Quantity		
	Filter Set Configurations	Tower I	Tower II	Tower III
Standard	Filter, pleated (24" x 24" x 6"), MERV 11 efficiency	4	8	12
Option A	Filter, pleated (24" x 24" x 2"), MERV 11 efficiency	12	24	36
Option B	Poly pre-filter with spring-loaded frame (24" x 24" x 2")	4	8	12
	Filter, pleated (24" x 24" x 2"), MERV 11 efficiency	8	16	24
Option C	Poly pre-filter with spring-loaded frame (24" x 24" x 2")	4	8	12
	Filter, pleated (24" x 24" x 4"), MERV 11 efficiency	4	8	12
Option D	Poly pre-filter with spring-loaded frame (24" x 24" x 2")	4	8	12
	Filter, mini-pleat (24" x 24" x 4"), MERV 11, 122 ft ²	4	8	12
Option E	Poly pre-filter with spring-loaded frame (24" x 24" x 2")	4	8	12
	HEPA, 99.97% filter, metal frame (24" x 24" x 4"), MERV 17, rated 1500 CFM	4	8	12
Option F	Poly pre-filter with spring-loaded frame (24" x 24" x 2")	4	8	12
	Filter, pleated (24" x 24" x 4"), MERV 14, synthetic, washable	4	8	12
Option G	Poly pre-filter with spring-loaded frame (24" x 24" x 2")	4	8	12
	Refillable Module (24" x 24" x 3"), holds 30 lbs. of charcoal	4	8	12
	Poly after-filter (24" x 24" x 1"), filter with plastic frame, MERV 17	4	8	12
Option H	Poly pre-filter with spring-loaded frame (24" x 24" x 2")	4	8	12
	Charcoal filter, impregnated (24" x 24" x 2")	8	16	24

Dimensions:

Top:



Front:



TOWER Free-standing Ambient Collection Module

Height to top of motor/blower

Tower I 62.50"
Tower II 80.50"
Tower III 104.50"
Width 31"
Depth 31"
Height, per Tower filter module 24
Height, AirPod base6"

Note: Specifications listed above may be modified to suit application. contact D.A.S. or representative for information.

Diversified Air Systems, Inc.

10801 Electron Drive, Louisville, Kentucky 40299

Toll free: (800) 264-8958

Tel.: (502) 267-0333 • Fax: (502) 267-4241

Website: www.diversair.com • email: info@diversair.com

Ambient Air Cleaner

APPLICATION PHOTOS









Note: Specifications listed above may be modified to suit application. contact D.A.S. or representative for information.

Diversified Air Systems, Inc.

10801 Electron Drive, Louisville, Kentucky 40299

Toll free: (800) 264-8958

Tel.: (502) 267-0333 • Fax: (502) 267-4241

Website: www.diversair.com • email: info@diversair.com